



FMAX212SS

TANDEM SUPER SINGLE GOOSENECK

Inspired by the “Super Single” trend in the trucking industry, the FMAX212SS is pound for pound the strongest single wheel gooseneck on the planet.

25,900 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102"
28' x 102", 30' x 102", 32' x 102", 35' x 102", 38' x 102"
40' x 102", 44' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 12,000 lb Heavy Duty, Oil Bath

COUPLER: 30,000 lb Bulldog BX1

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 16" Engineered Beam 2.0

JACK: 2 - 12,000 lb Drop-Leg Jacks

NECK: 12" Engineered Neck

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

STORAGE: Diamond Plate Neck Box with Gas Shock Assisted Lid

SWAY CONTROL: Standard on 30' - 44' models

TIRES: ST235/75R17.5 18 Ply Radial, Super Single

DM POWDER COAT

STANDARD COLORS								
	ONYX BLACK	ARTIC WHITE	SCARLET RED	CEMENT GRAY	CARBON METALLIC GRAY	PLATINUM SILVER METALLIC	MOCHA METALLIC	DYNAMIC BLUE METALLIC
SPECIAL COLORS								
	COMMERCIAL YELLOW	TRACTOR GREEN	INDUSTRIAL ORANGE	LIME GREEN	TACTICAL TAN	CUSTOM		

AVAILABLE WHEELS



BLACK

POPULAR UPGRADES

Electric-Over-Hydraulic Disc Brakes

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Blackwood Floor

2 - 10,000 lb Hydraulic Jacks

14" x 14" x 36" Under-Slung Box

Air Ride Suspension

