









www.diamondc.com





PX216

TANDEM DUAL WHEEL PINTLE HITCH

STANDARD

It's simple, the PX216 is heavy duty without the heavy weight. Haul more.

30,000 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102"

28' x 102" 30' x 102", 32' x 102", 35' x 102"

38' x 102", 40' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 16,000 lb Heavy Duty, Oil Bath

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 16" Engineered Beam 2.0 20' - 32' 18" Engineered Beam 2.0 35' - 40'

JACK: 2 - 12,000 lb Drop-Leg Jacks

LACE RAIL: 6" Channel

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets

and Pipe Spools

STORAGE: HD V-Tongue Lid with Gas Shock Assist in Tongue


SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST215/75R17.5 16 Ply Radial, Dually

TONGUE: 16" Engineered Tongue w/60K Pintle Eye



DM POWDER COAT



AVAILABLE WHEELS



INDUSTRIAL

TRACTOR

BLACK



CUSTOM

MOCHA

METALLIC

METALLIC

ALUMINUM OUTER WHEELS

POPULAR UPGRADES

40,000 lb GVWR Package

Electric-Over-Hydraulic Drum Brakes

Blackwood Floor

2 - 25,000 lb Two Speed Drop-Leg Jacks

14" x 14" x 36" Under-Slung Box

Air Ride Suspension @ SUPEWELL

